

Bullhorn Remote Monitoring Data Communication



American Innovations' **Bullhorn AMR6** monitors assets in the oil & gas industry and communicates measurement results by utilizing reliable digital cellular or satellite networks. The units feature 6 digits of meter resolution for accurate, reliable daily reading of gas volume through industrial or commercial positive displacement (PD) meters. The AMR6 also tracks the daily volume of barrels through a LACT meter which allows producers to balance their entire system. For applications outside of oil & gas metering, AI recommends the **APM4AM** and **RM2020** for general purpose monitoring.



Applications

- ✓ **Oil & Gas assets, including:**
 - Gas meters (commercial and industrial)
 - Lease Automatic Custody Transfer (LACT) meters

Features	Benefits
Inputs: 1 dry contact closure or digital - accumulates up to a 6 digit reading	Measure data from gas meters and LACT meters
Daily reporting of measurement results	Daily tracking of gas usage and/or oil volume
Data communication via digital cellular or satellite (Inmarsat) network	Reliable, cost-effective data communication
Power: sealed lead-acid battery with solar or AC charger; optional lithium battery for cellular model	Long term product reliability & easy installation
Bullhorn Asset Tracker (BAT™) system communicates unit status by email, voice and/or text notifications	Notifications on equipment status eliminate remote site visits
Proven backend system for data storage with disaster recovery	Bullhorn unit data stored for 18 months
BAT™txt and BAT™mobile included	On-the-go access to BAT™ via smartphone and in remote areas with low signal strength

AMR6	Specifications Summary
Inputs	1 Dry Contact Closure or Digital: Accumulates up to a 6 digit reading Dry contact: <ul style="list-style-type: none"> •22µA source current •Max rate = 2.5 cycle/sec. , Min. width = 100 millisecond/state change Digital channel: <ul style="list-style-type: none"> •Logic 1 = 2Vmin, Logic 0=800mVmax •Accumulator: Max. input = 1 cycle/2 sec., Min. Width = 1 sec/state change •Scan rate: each channel is read once per second
Communications	•GSM Digital Cellular •Inmarsat Satellite •Orbcomm Satellite
Software Interface	Bullhorn Asset Tracker website. AI network operations center.
Power Supply	•Sealed lead-acid gel cell battery w/ solar or AC charger. Optional lithium battery for GSM unit.
Dimensions	•Satellite unit: Polycarbonate box enclosure (8.5 X 6.5 X 4 .5") •Cellular unit: Polycarbonate box or anodized aluminum an (3.66 X 5.5" without antenna)
Data Integrity	Data stored in non-volatile (EEPROM) memory
Environment	Temperature: -30 degrees C to +70 degrees C. Humidity: 0-100% non-condensing.
Compliance	FCC Part 15. Enclosure - NEMA 4X compliant. ESD: 8kV Air/ 4kV Contact.

Services. American Technical Service Engineers provide: Technical support via phone and email | Bullhorn installation Services | Customer training (on-site and in Austin, TX) | Bullhorn Asset Tracker (BAT) data services

About American Innovations. American Innovations (AI) provides oil and gas companies with critical knowledge and decision support for assets and infrastructure via corrosion protection and integrity management services. The company supplies products and services to automate the collection, storage, and reporting of equipment and pipeline compliance data. Bass Engineering, a subsidiary of American Innovations, offers Cathodic Protection engineering services. American Innovations product lines include: Pipeline Compliance System (PCS), Allegro Field Data PC®, Bullhorn® Remote Monitoring, MicroMax® Current Interrupters, and Integrity Management via Risk Intelligence™ Software and Integrity & Compliance Services.

Product	Application	Comm. Method	Features
Bullhorn RM2020	General purpose	Orbcomm satellite	4 Analog Inputs, 2 Digital Inputs, Solar & AC power with battery backup
Bullhorn RM4010	Cathodic Protection, two-way with interruption	Inmarsat satellite	Low-latency worldwide coverage, 4 Analog Inputs, 2 Digital Inputs, GPS-based current interruption, AC power with battery backup
Bullhorn RM4020	Low-cost Cathodic Protection monitoring	Orbcomm satellite	Low-cost worldwide coverage, 4 Analog Inputs, 2 Digital Inputs, Solar & AC power with battery backup
Bullhorn AMR6	Gas measurement	Inmarsat & Orbcomm satellite Digital cellular	6 digital accumulator or Digital Input, Solar, AC, or Lithium battery power options
Bullhorn APM4AM	General purpose	Inmarsat satellite Digital cellular	Analog Inputs, 2 Digital Inputs, Solar & AC power with battery backup
Bullhorn APM4AM-SAT WS	General purpose & Agriculture	Inmarsat satellite	7 wireless digital inputs, Solar & AC power with battery backup
Bullhorn SDT16	Compressor, oil & gas equipment	Inmarsat & Orbcomm satellite Digital cellular	Supports Modbus, Mercury, Dresser, and Reynolds protocols communication, up to 16, 6-bit registers or 8, 12-bit registers, 1 digital input

SALES: Bullhorn & MicroMax - Oil & Gas - US & Canada: **Paul Lucco** paul.l@aiworldwide.com (713)705-1875
Bullhorn & MicroMax - Oil & Gas- All Other Countries and All Other Markets (Water/Wastewater, Ag, Irrigation):
Neil Pickthall neil.p@aiworldwide.com (832)656-4225

Bullhorn Product Data Sheet: Bullhorn AMR6

5/24/2011 **Note: Product specs are subject to change without notice.**